

DC CHAIN DRIVE GARAGE DOOR OPENER

Trusted reliability and quiet operation.



WARRANTY

4-YEAR
Motor

1-YEAR
Parts and
Accessories

RELIABLE



CUSTOMIZED DC MOTOR IS PURPOSEFULLY DESIGNED AND BUILT TO LAST.

CHAIN DRIVE SYSTEM FOR STEADY PERFORMANCE AND INDUSTRIAL STRENGTH.

SOFT START/STOP FOR SMOOTH OPERATION.

SMART



MONITOR AND CONTROL THE OPENER FROM ANYWHERE USING MOBILE DEVICES.

FREE MyQ® MOBILE APP SO USERS KNOW THEIR HOME IS SECURE.

REAL-TIME ALERTS INDICATE THE STATUS OF THE GARAGE DOOR VIA EMAIL OR PUSH NOTIFICATIONS.

SECURE

Security+ 2.0®

SAFEGUARDS GARAGE ACCESS BY SENDING A NEW CODE WITH EVERY CLICK.

POSILOCK® ELECTRONICALLY PROTECTS AGAINST FORCED OPENINGS.

ALERT-2-CLOSE SIGNALS WHEN A DOOR IS BEING CLOSED BY MyQ.

THE PROTECTOR SYSTEM® INVISIBLE LIGHT BEAM AUTO-REVERSES THE DOOR IF THERE IS AN OBSTRUCTION.

INCLUDED ACCESSORIES:


MULTI-FUNCTION CONTROL PANEL®  **882LMW**
Turns on garage door opener lights from inside the garage.


3-BUTTON REMOTE CONTROL  **893LM**
Operates up to 3 openers or MyQ Light Accessories.


POWERFUL ADD-ONS:

MINI UNIVERSAL REMOTE CONTROL  **374UT**
Compact and portable to provide quick, easy garage access.

INTERNET GATEWAY  **828LM**
Connects the opener to the Internet, enabling smartphone control.

REMOTE LIGHT CONTROL  **825LM**
Enables home lighting control through a garage remote or a smartphone.

REMOTE LIGHT SWITCH  **823LM**
Replaces an existing wall switch to enable home lighting control with a garage remote or a smartphone.

GARAGE DOOR AND GATE MONITOR  **829LM**
Monitors and closes up to 4 garage doors from any room in the house.

MASTERFUL ENGINEERING.

MOTOR



- 12VDC
- 53 RPM
- Automatic Thermal Protection
- Permanent Lubrication

POWER



- 120VAC
- 60 Hz Voltage
- 2.7A Current Rating
- UL Listed
- 4' Power Cord (3-Prong)

MECHANICS



- **Steel Chassis, T-Rail and Trolley**
- **Full Chain Drive Mechanism** (63:1 Gear Reduction and Adjustable Door Arm)
- **Auto-Force** Adjustment for Changing Weather and Environmental Conditions
- **Electronic Limits** for Easy Setup
- **DC Logic Board** with Built-In Surge Suppressor

7.67"



15.2"

10.9"

DIMENSIONS

Rail Options	7'	8'	10'
Installed Length	128"	140"	164"
Max. Opening	7'6"	8'6"	10'6"

Headroom Clearance Required: 2"

8"

Per second
for door
to move
upward

SPEED

6.5"

Per second
for door
to move
downward

STANDARD SPECS.

SECURITY

SECURITY+ 2.0® RADIO CONTROLS

3-Button Remote Control (893LM)

Operating Range: ~200'

Operating Temperature: -40°F to 150°F
Frequency:

- Remote Control: 310, 315 and 390 MHz Tri-Band
- Garage Door Opener: Frequency Agile on 310, 315 and 390 MHz
- Security+ 2.0 Anti-Burglary Coding

SECURITY+ 2.0 ENCRYPTED CONTROLS

Multi-Function Control Panel® (882LMW)

- Program Remote Controls
- Maintenance Alert System

SMART

MyQ® RADIO

50-Channel FHSS
(Frequency Hopping Spread Spectrum)

- Provides 2-way communication from garage door opener and MyQ Accessories.
- Enables monitoring and control of garage door openers and lighting controls via smartphone, tablet or computer.*

*Requires Internet Gateway (828LM)

HOMELINK® COMPATIBLE (VERSION 4.0 OR HIGHER*)

*May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.

ELECTRICAL

LIGHTING



100W

- 1 100-Watt Lightbulb
- Adjustable Time, Solid-State Delay
- Enhanced CFL (Compact Fluorescent) Compatible, Max. 27 Watts

ENERGY EFFICIENCY

- Approximately 1-Watt Power in Standby Mode*

*Occurs at Down Limit When Opener's Lights Turn Off

SHIPPING.

SHIPPING WEIGHT (in lbs.)

18
HEAD20
RAIL (X')

CARTONS (2)

CARTON 1: 20" x 12" x 10"

- Multi-Function Control Panel (882LMW)
- 3-Button Remote Control (893LM)
- Garage Door Opener Head (8160)
- The Protector System® Safety Reversing Sensors

CARTON 2: 10'4" x 5" x 5"

- Assembled Solid-Steel Chain T-Rail

CONVENIENCE AND SAFETY.



- Alert-2-Close Unattended Close Operation*
- Hands-Free Work Lights On
- Emergency/Quick Release
- Automatic Trolley Reconnect
- Ventilation/Pet Opening
- Down Safety Reverse
- Up Safety Stop
- Safety Beam Break Turns Lights On
- Maintenance Alert System

*Unattended Operation functionality cannot be utilized when opener is installed on a one-piece door.