DC BATTERY BACKUP CAPABLE CHAIN DRIVE WI-FI® GARAGE DOOR OPENER

Advanced security and reliable performance.



Battery Sold Separately

DC MOTOR IS PURPOSEFULLY DESIGNED AND BUILT TO LAST.

CHAIN DRIVE SYSTEM FOR STEADY PERFORMANCE AND INDUSTRIAL STRENGTH.

BATTERY BACKUP CAPABILITY ENSURES ACCESS DURING POWER OUTAGES (REQUIRES BATTERY BACKUP).

SOFT START/STOP FOR SMOOTH OPERATION.



FREE MyQ® MOBILE APP SO USERS KNOW THEIR HOME IS SECURE.

BUILT-IN WI-FI FOR THE EASIEST WAY TO CONNECT THE GARAGE.

REAL-TIME ALERTS INDICATE THE STATUS OF THE GARAGE DOOR VIA EMAIL OR PUSH NOTIFICATIONS.

MONITOR AND CONTROL THE OPENER FROM ANYWHERE USING MOBILE DEVICES.

Security+ 2.0°

SAFEGUARDS GARAGE ACCESS BY SENDING A NEW CODE WITH EVERY CLICK.

POSILOCK® ELECTRONICALLY PROTECTS AGAINST FORCED OPENINGS.

ALERT-2-CLOSE SIGNALS WHEN A DOOR IS BEING CLOSED BY MyQ.

MOTION DETECTOR LIGHTS THE WAY AUTOMATICALLY.

THE PROTECTOR SYSTEM® INVISIBLE LIGHT BEAM AUTO-REVERSES THE DOOR IF THERE IS AN OBSTRUCTION.

INCLUDED ACCESSORIES:

MOTION DETECTING **CONTROL PANEL®**

Activates the opener's lights automatically.





Operates up to 3 openers or MyQ Light Accessories.



POWERFUL ADD-ONS:

BATTERY BACKUP

Powers up the opener when the power's out.





REMOTE LIGHT CONTROL

Enables home lighting control through a garage remote or a smartphone.



GARAGE DOOR AND GATE MONITOR

Monitors and closes up to 4 garage doors from any room in the house.





MINI UNIVERSAL REMOTE CONTROL

Compact and portable to provide quick, easy garage access.



WIRELESS KEYLESS ENTRY

Provides convenient, secure access from outside the garage with a 4-digit PIN.







DC Battery Backup Capable Chain

Drive Wi-Fi® Garage Door Opener

MASTERFUL ENGINEERING.

MOTOR



- -12VDC
- -53 RPM
- Automatic Thermal Protection

POWER -



- -60 Hz Voltage
- -2.7A Current Rating
- UL Listed

-120VAC

-4' Power Cord (3-Prong)



MECHANICS

- Steel Chassis, T-Rail and Trolley
- Full Chain Drive Mechanism (63:1 Gear Reduction and Adjustable Door Arm)
- Auto-Force Adjustment for Changing Weather and **Environmental Conditions**
- Electronic Limits for Easy Setup
- DC Wi-Fi Logic Board with Built-In Surge Suppressor

DIMENSIONS

Rail Options	7'	8'	10'
Installed Length	128"	140"	164"
Max. Opening	7'6"	8'6"	10'6"

Headroom Clearance Required: 2"

Per second for door to move upward

SPEED

Per second for door to move downward

STANDARD SPECS.

SECURITY+ 2.0® RADIO CONTROLS

3-Button Remote Control (893LM)

Operating Range: ~2001

Operating Temperature: -30°F to 150°F Frequency:

- Remote Control: 310, 315 and 390 MHz Tri-Band
- Garage Door Opener: Frequency Agile on 310, 315 and 390 MHz
- -Security+ 2.0 Rolling Code Technology

MyQ® RADIO



- Provides 2-way communication from garage door opener and MyQ Accessories.
- Enables monitoring and control of garage door openers and lighting controls via smartphone, tablet or computer.

HOMELINK® COMPATIBLE (VERSION 4.0 OR HIGHER*)

*May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.

LIGHTING





- Max. 2 100-Watt Lightbulbs
- Adjustable Time
- Enhanced CFL (Compact Fluorescent) Compatible, Max. 27 Watts
- Disabled in Battery Backup Mode

ENERGY EFFICIENCY

- Approximately 1.5-Watt Power in Standby Mode*
- *Occurs at Down Limit When Opener's Lights Turn Off

ENCRYPTED CONTROLS

Motion Detecting Control Panel® (886LMW)

- Program Remote Controls
- Maintenance Alert System
- Easy Wi-Fi Setup

SECURITY+ 2.0

SHIPPING.

SHIPPING WEIGHT (in Ibs.)



CARTON 1: 20" x 12" x 10"

- Motion Detecting Control Panel (886LMW) -3-Button Remote Control (893LM)
- Garage Door Opener Head (8360W)
- -The Protector System® Safety Reversing Sensors

HEAD

RAII

BATTERY

BACKIIP

(OPTIONAL)

CARTON 2: 10'4" x 5" x 5"

- Assembled Solid-Steel Chain T-Rail CARTON 3 (OPTIONAL): 5.31" x 4.63" x 5.13"

-Battery (485LM)

CONVENIENCE AND SAFETY.



- Motion Detection Feature on Control Panel
- Emergency/Quick Release
- Automatic Trolley Reconnect
- Ventilation/Pet Opening
- Down Safety Reverse

- Safety Beam **Obstruction Turns** Liahts On
- Maintenance Alert System
- Garage Door Opener Capacity of up to 24 Remote Controls, 2 Wireless Keyless Entry Systems and 16 MyQ Devices



Wi-Fi® is a registered trademark of Wi-Fi Alliance



HomeLink® and the HomeLink House® logo are registered trademarks of Gentex Corporation LMGDPG8360W